



**E+** Extended Range.  
Expanded Opportunities.



## Smoke/Heat/Freeze Detector

Unlock new business potential with  
E+ Extended Range sensors by 2GIG<sup>®</sup>

The E+ Smoke/Heat/Freeze Detector now has 900MHz spectrum as part of the new line of E+ Extended Range sensors. The E+ series provides expanded, reliable security coverage to large, multi-level homes and commercial facilities, bringing peace of mind to clients and new business opportunities for integrators. Enhancements to the new sensors include increased battery life, two-way encryption for enhanced security, and a user-friendly enrollment process that lowers installation time and reduces truck rolls.



Learn more



E+ SERIES WORKS WITH  
**2GIGEDGE**

# 2GIG-SMKT-900

## Smoke/Heat/Freeze Detector



### SPECIFICATIONS

|                               |   |
|-------------------------------|---|
| Transmitter Frequency         | 904MHz - 922MHz   |
| Compatibility                 | 2GIG EDGE Panel (FW 1.3 or later is required)                             |
| Supervisory Interval          | 70 minutes  |
| Dimensions (D x H)            | 4.7 x 2.3 inches (120 x 58 mm)  |
| Weight                        | 0.46 lbs  |
| Audible Alarm                 | > 85dB (A) at 10ft (3m) minimum   |
| High Temperature Level        | 134°F +/- 4°F   |
| High Temperature Rate of Rise | Above 104°F and Increases 15°F or more in one minute                      |
| Low Temperature Warning       | At or below 40°F for up to 1 minute<br>Restore at 45°F for up to 1 minute |
| Ambient Temperature           | -40° to 100°F (4.4°C to 37.8°C)   |
| Operating Rel. Humidity       | 15% to 95%, non-condensing  |
| Batteries                     | 2 x CR123A  |
| Regulatory Listing            | UL268 7th Edition, CAN/ULC S529 7th Edition, CSFM                         |

### FEATURES:

- **Extended Range** of up to 1.2 miles\* with **900MHz** spectrum
- Supports UL268 7th edition requirements
- One Go/All Go communication enables all E+ smoke detectors to collectively sound an alarm, ensuring swift response and maximizing urgency
- Monitors and reports excessive temperature variances including rate of rise, which is triggered once room temperature is 104° F
- Optical smoke detection chamber for improved smoke detection and recognition of smoke from some synthetic materials
- Battery life of up to 3 years
- Two-way encrypted communication for enhanced security and reliability

\*Range can vary depending on building materials

E+ SERIES WORKS WITH  
**2GIGEDGE™**

**E+ Extended Range** sensors offer more extensive security coverage for larger residential and commercial properties to keep clients feeling secure. With sleek, modern designs that seamlessly integrate into any environment, the E+ series includes indoor and outdoor contact sensors, and motion, glass break and smoke detectors. Paired with the innovative 2GIG EDGE™ panel, this smart security solution combines versatility, innovation, and reliability.

### ADDITIONAL E+ SENSORS:



**DW10E-900**  
Indoor Door/  
Window Contact



**DW30E-900**  
Outdoor Wireless  
Contact Sensor



**PIR1E-900**  
Passive Infrared  
Motion Detector



**GB1E-900**  
Glass Break  
Detector



[2GIG.com](http://2GIG.com)

[Niceforyou.com](http://Niceforyou.com)

