

4K-PTZDT

4K UltraHD Active Deterrence Mini PTZ Weatherproof IP Security Camera with a 4X Motorized Zoom and 2-Way Audio



PRODUCT HIGHLIGHTS

4K UltraHD resolution and 4x optical zoom provide crystal clear footage

PTZ (pan, tilt, zoom) capabilities allow you to get an even closer look at suspicious activity

A compact housing and flexible installation means this PTZ is perfect for many scenarios, for homes or businesses

AI-assisted intelligent events provide real-time alerts of potential threats

Active deterrence strobe lights and siren for alerting unwelcome guests of the camera's presence

Built-in microphone and speaker for 2-way audio communication

IP66 weatherproof and IR distance of 50m (164 feet) make this camera suitable for any condition

ONVIF compatibility allows for easy integration into existing security systems

Affordable and easy to use, with all the normal R-Series features like mobile viewing and simple installation



PRODUCT SPECIFICATIONS

Product Model	4K-PTZDT
Highest Resolution	8MP (4K) 3840(H)×2160(V)
Image Sensor	1/2.7" Progressive CMOS
Min. Illumination	Color 0.002lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Lens	2.8mm - 12mm
F No.	F 1.6
WDR	120dB true WDR
Video Compression	H.265 / H.264
Video Bit Rate	246 Kbps ~ 16 Mbps
Resolution	Triple Streams Supported: Main Stream (1-15fps optional) 8MP (3840x2160), 5MP (3072x1728), (2592x1944), 4MP (2592x1520), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), Sub Stream 720P (1280x720), VGA (640x480), QVGA (320x240) Mobile Stream VGA (640x480), QVGA (320x240)
AI Intelligent Events	Face detection, people & vehicle detection, line crossing, intrusion, stationary object, people counting, heat map, crowd density, queue detection
Active Deterrence	On board strobe lights and siren
System Compatibility	ONVIF compatible
Interface	RJ45 10M / 100M Ethernet interface
IR LED Range	Up to 165 ft
Weatherproof Rating	IP66
Power Supply	DC12V or POE
Audio	Built-in microphone and speaker
Edge Storage	Up to 256 GB
PTZ Mobility	Pan (0° - 355°); Tilt (0° - 90°); Zoom (2.8mm - 12mm)
Operating Temperature	-4~140°F
Dimensions	9 1/2" x 4 1/2"