

Perfect choice for Access Control

Akuvox's X916S is designed to provide a visually stunning and intuitive user-experience. It brings a number of innovative new features to provide a fully customizable solution for occupant and visitor access control in condominiums, apartment buildings, office buildings, gated communities and industrial buildings.

At a Glance

- Vandal resistant body with 13inch touchscreen;
- Android operation system;
- Wide-angle camera: 115° (H), 63° (V);
- Two-way audio communication over IP networks with Echo Cancel feature;
- Multi-way access feature including: Face, EM/Mifare Card, PIN, BLE & QR code;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;



Physical & Power

- | | |
|--|---|
| • Front Panel: 316 grade stainless steel | • HDMI Interface: 1 |
| • Display: 13 Inch IPS LCD | • TF Card Slot: 1 |
| • Main Camera: 2M pixels, with starlight | • BLE: Support BT5.0 |
| • Auxiliary Camera 1: 2M pixels | • Tamper Alarm: Support |
| • Auxiliary Camera 2: 0.3M pixels | • Microphone: 2 |
| • Light Sensor: Support | • Speaker: 2 |
| • Motion Sensor: Support | • Power: 12V / 500mA (Max.) |
| • Wiegand port: 1ch input/output (selectable) | • Ethernet port: 2xRJ45, 10/100/1000Mbps adaptive |
| • RS485 port: Support | • 802.3at Power-over-Ethernet |
| • RF reader: 13.56MHz&125kHz, NFC (only Android) | • IP Rating: IP65 |
| • Relays out: 4 | • IK Rating: IK08 |
| • Inputs: 4 | • Installation: Flush-mounted & Wall-mounted |
| • Reset button: 1 | • Dimension(HxWxD): 339.2x383.9x45.8mm |
| • USB Interface: 2 | • Working Humidity: 10~90% |
| | • Working Temperature: -20°C ~ +55°C |
| | • Storage Temperature: -40°C ~ +70°C |

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.8", CMOS for main camera
- Pixels: CIF, QCIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video technology: HDR
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p – 30fps
- Viewing angle: 115°(H) / 63°(V)
- Compatible to 3rd-Party-Video components, e.g. NVRs

Networking and Protocol

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Door Entry Feature

- Relays controlled individually by DTMF tones
- Multi-way Unlock: Face, EM/Mifare Card, PIN, QR & BLE
- Camera permanently operational
- White balance: auto
- Minimum illumination: 0.1LUX

Capacity

- User: 20,000
- Face Templates: 20,000
- Card: 100,000
- PIN: 20,000

Card Type

- EM card
- Mifare card
- DesFire card (EV1/EV2/EV3)

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)