QUADPANO1


32MP Panoramic Vandal Dome IP Camera with Lights for 24/7 Full Color, IR Night Vision, Al Intelligent Events, 2.8~12 mm Motorized Lenses







- Four adjustable lenses in a single camera housing, covering up to a 360° panoramic field of view
- Four 8MP 4K UltraHD stream outputs (3840 x 2160)
- Four-channel starlight and 120dB true WDR
- The all-in-one design gives you multi-channel functionality under a single IP address
- Each channel has a variety of intelligent events which can all be enabled simultaneously
- Built-in dual source illuminator, giving you the choice between IR and white light illumination
- IP67 and IK 10 rated, making this camera ideal for a wide variety of scenarios



IP66

IK10

PoE



VIDEO	
Main Stream	50/60Hz: 25fps 8MP(3840x2160), 5MP(2592x1944, 3072x1728), 4MP(2592x1520), 3MP(2304x1296), 1080P(1920x1080), 960P(1280*960), 720P(1280x720)
Sub-Stream	50/60 Hz: 25fps 720P(1280x720), VGA(640x480), QVGA(320x240)
Video Compression	Main stream: H.265+, H.265, H.264+, H.264 Sub stream: H.265+, H.265, H.264+. H.264. MJPEG
Video Bit Rate	8Kbps to 16 Mbps
H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
Region Of Interest (ROI)	Yes

QUADPANO1

32MP Panoramic Vandal Dome IP Camera with Lights for 24/7 Full Color, IR Night Vision, AI Intelligent Events, 2.8~12 mm Motorized Lenses



ILLUMINATION	
Supplement light type	IR and warm light
Supplement light range	Up to 100ft (IR) / 50ft (warm light)
IR Wavelength	850 nm
Smart Supplement Light	Yes

AUDIO	
Audio Compression	G.711
Audio Bit Rate	Auto
Sampling Rate	8 kHz
Environment Noise Filtering	Yes

NETWORK	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP, PPPoE
Simultaneous Live View	Up to 92 streams
User/Host	Up to 32 users. 2 user levels: administrator and user
API	ONVIF (Profile S/G/T)
Web Browser	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above

ÉVE	NT
Basic Event	Motion Detection
Smart Event	Face Recogntion, Pedestrian & Vehicle Detection, Line Crossing, Object Detection, Cross Counting, Heat Map, Crowd Density, Queue Length, License Plate Recognition, Intrusion, Region Entrance, Region Exi□ng

IMAGE	
Image Settings	Rotate mode, saturation, brightness, contrast, sharpness, and white balance are adjustable by client software or web browser
Day/Night Switch	Day/Night/Image/Schedule
Wide Dynamic Range (WDR)	120 dB
Image Enhancement	BLC, 3D DNR, HLC

INTERFACE	
Network Connection	1 RJ45 10M/100M/1000M Ethernet port
On-Board Storage	Built-in Micro SD/SDHC/SDXC slot, up to 256GB
Audio	1 input (RCA), 1 output (RCA)
Alarm	2 inputs, 2 outputs
Reset	Yes

GENERAL	
Power	ACV24 / DCV12 / PoE++
	Power consumption: Max 43W
Material	Alloy
Dimensions	Ø 300 mm × 195 mm (11.8" x 7.7")
Package Dimension	500 mm × 395 mm × 385 mm (19.7" x 15.6" x 15.2")
Weight	Approx. 4.6kg(10.1lb)
Operating conditions	-30~+55°C/less than ≤ 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10


QUADPANO1


32MP Panoramic Vandal Dome IP Camera with Lights for 24/7 Full Color IR Night Vision, Al Intelligent Events, 2.8~12 mm Motorized Lenses







DIMENSIONS









Outdoor