



- ↳ 19" patch panel surge protector for POE-A
- ↳ 32 ports
- ↳ In/Out front : RJ45
- ↳ Maintenance possible per port
- ↳ Secondary Protection
- ↳ UL497B

Electrical Characteristics		
Insertion loss		< 1 dB
Max. load current @25°C	IL	750 mA
Max. capacitance	C	< 25 pF (ligne ethernet)
Capacity Maximum	pF	<25
Telecom Discharge Current 10/1000	kA	0,05
Telecom Total Discharge Current 10/1000	kA	0,05
Telecom Discharge Current 10/1000	kA	0,05
Telecom Discharge Current 10/1000	kA	0,05
Max Discharge Current Imax (8/20µs x 1)	kA	0.0500
Installation		
Operating TemperatureMin	°C	-40.0000
Operating TemperatureMax	°C	85.0000
Operating TemperatureMin	°F	-40.0000
Operating TemperatureMax	°F	85.0000
Operating Relative HumidityMax	%RH	95
Operating AltitudeMin	Ft	2000.0000
Operating AltitudeMax	Ft	6500.0000
Housing/Enclosure material		aluminum
Mounting		Rack mount
IP Environmental rating/IP		IP20
Installation Location		indoor
Product DimensionL	mm	483.0000
Product DimensionH	mm	88.0000
Product DimensionL	In	19.0200
Product DimensionH	In	3.4650
Miscellaneous		
Individual Pack		Yes
Storage TemperatureMin	°C	-40.0000
Storage TemperatureMax	°C	85.0000
Storage TemperatureMin	°F	-40.0000
Storage TemperatureMax	°F	85.0000
Installation		
Cable type		Ethernet
Part number		
6372		

