



### Universal Request-To-Exit PIR

The REX sensor is specifically designed for indoor Request-To-Exit applications and features a passive infrared sensor with qualified motion analysis. The sensitivity of the REX sensor can be easily adjusted for long or short-range applications and features an adjustable time delay. Because of its sleek design, the REX sensor can be easily mounted to any frame, header wall, or ceiling.



### Model

PN: REXM

### Specifications:

#### Relay

Output: 2C Contact(N.C/N.O), 24VDC 1A Max.  
Hold Time: 0.5-64 seconds

#### Detection Type

Passive infrared

#### Coverage Range

12 x 5' at 7' high, 30 x 12' at 15ft high (adjustment)

#### Environmental

Humidity: 0 - 95% relative humidity non-condensing

#### Enclosures

Dimensions: (W x H x D) 6.53" x 1.57" x 1.53"  
Weight: 0.4 lbs / 6.4 oz / 182 g  
Plastic Enclosure

#### Power

12-24VDC or VAC

### Manufacturer's Limited Warranty

One to three-year warranty against defects in materials and workmanship.  
For full details, visit [www.prodatakey.com/warranty](http://www.prodatakey.com/warranty)

Visit [www.prodatakey.com/resources](http://www.prodatakey.com/resources) to access marketing, installation, and support resources.  
For questions about the REX sensor, please contact [support@prodatakey.com](mailto:support@prodatakey.com).